

Conservation Logger

Product Specifications

Type: Four-Channel Temperature, RH and 0-5 VDC (2x)

GENERAL SPECIFICATIONS

Size:	107 mm x 74 mm x 22 mm (4.2" x 2.9" x 0.9")
Weight:	110 grams (3.75 ounces)
Case Material:	Noryl® plastic
Battery:	3.6 volt Lithium
Resolution:	12-bit (1 part in 4096)
Mounting:	Magnetic backing or lock eyelet
Clock Accuracy:	+/- 2 seconds per day
Sampling Methods:	Continuous (First-in, First-out)*, Stop When Full (Fill-then-stop) <i>*Not available with sample rates faster than eight seconds</i>
Operating Limits:	-40 to 70°C (-40 to 158°F) and 0 to 95% RH (non-condensing)
PC Requirements:	IBM PC or 100% compatible with at least one free serial port, 2 MB of RAM memory, and 2 MB of hard disk space
Software Requirements:	TrendReader® Standard (compatible with Windows® 3.1, 95, 98, Me, NT, 2000, and XP)

Memory Size:	128KB (capable of storing 87,000 readings)
Sampling Rates:	User selectable rates from 25 per second to once every eight hours (BP-101 battery pack or PS-201 power supply required for sampling rates faster than eight seconds)
Number of Channels:	Four (one for the internal temperature sensor, one for the internal RH sensor, and the remaining two channels are reserved for external sensors with 0-5 VDC output)

SENSOR SPECIFICATIONS

Temperature Sensor:	NTC Thermistor
Range:	-40 to 70°C (-40 to 158°F)
Accuracy:	+/- 0.2°C from 0 to 70°C; +/- 0.5°C from -40 to 0°C (+/- 0.36°F from 32 to 160°F; +/- 0.9°F from -40 to 32°F)
Resolution:	0.03°C at 25°C (0.05°F at 77°F); better than 0.07°C (0.12°F) between -25 and 70°C (-13 and 158°F); better than 0.13°C (0.23°F) between -40 and -25°C (-40 and -13°F)
RH Sensor:	Capacitive thin polymer film
Range:	0 to 95% RH
Accuracy:	+/- 3% RH from 10 to 90% (-20 to 40°C [-4 to 104°F])
Resolution:	Better than 0.04% between 25 and 60% RH at 25°C (77°F)
External Sensors (2):	
Range:	Any 2 sensors with a 0-5 VDC output

The Conservation Logger is a self-contained temperature and relative humidity logger with two external channels for use with a variety of sensors. It is equipped with an LED light that will alert the user if measurements fall above or below user set limits.



WARRANTY

Internal Battery:	5 Years
Data Logger:	3 Years

APPLICATIONS

Monitoring indoor air quality, conserving and/or preserving precious artifacts and paintings*
*(*when combined with a light sensor)*

Model#:	Cat#:
Conservation Logger	01-0133

AGENTS TRANSECON (AXIO)

Unit 1, 13/F., Sing Win Factory Building
15-17 Shing Yip Street, Kwun Tong

Kowloon, Hong Kong
Tel : (852) 2892-1992 Fax : (852) 2836-0448
E-mail : kmccatal@hkabc.net

Web site : <http://www.axiom.com.hk>